

# MR PN 10

## Maximum capacity table



### MR 25 PN 10

Outlet pressure [mbar]	Accuracy class	Inlet pressure [mbar]						
		100	500	1000	3000	5000	7000	10000
22	AC10	21	46	77	143	184	261	358
50	AC10	23	63	94	184	252	325	426
100	AC10	-	48	88	187	305	393	494
300	AC10	-	36	65	171	253	363	496
500	AC10	-	-	82	224	344	463	657
100	AC5	-	33	60	126	198	264	423
300	AC5	-	23	39	97	156	194	363
500	AC5	-	-	45	134	209	329	418

Nm<sup>3</sup>/h

### MR 50 PN 10

Outlet pressure [mbar]	Accuracy class	Inlet pressure [mbar]						
		100	500	1000	3000	5000	7000	10000
22	AC10	100	204	266	470	797	1022	1308
50	AC10	52	126	189	409	756	1049	1259
100	AC10	-	177	264	560	835	994	1472
300	AC10	-	97	168	428	726	985	1361
500	AC10	-	-	257	717	1075	1434	1942
100	AC5	-	110	154	352	637	824	1187
300	AC5	-	52	104	246	389	648	907
500	AC5	-	-	149	358	657	896	1270

Nm<sup>3</sup>/h

## Your contacts

Germany  
Elster GmbH  
Steinern Str. 19 - 21  
55252 Mainz-Kastel  
T +49 6134 605 0  
F +49 6134 605 223  
www.elster-instromet.com  
info@elster-instromet.com

Belgium  
Elster-Instromet N.V.  
Rijkmakerlaan 9  
2910 Essen  
T +32 3 670 0700  
F +32 3 667 6940  
www.elster-instromet.com  
info@elster-instromet.com

Singapore  
Elster-Instromet Sdn. Bhd. (Singapore Branch)  
160 Paya Lebar Road  
#04-01 Orion@Paya Lebar  
Singapore 409022  
T +65 6247 7728  
F +65 6247 7729  
sales@elster-instromet.com.sg



MR PN10 MCT EN02

A17.10.2008

Subject to change without prior notice  
All rights reserved

73030214